

Damp Proofing System - Gives Moisture No Chance!...

SPECTRUM

Product Development For Damp Slabs

No More Need For Moisture Tests!

[View this email in your browser](#)

SYSTEMATIC SOLUTIONS

SPECTRUM'S UZIN DAMP-PROOFING SYSTEM GIVES MOISTURE NO CHANCE!

Fast & Simple Installation,
Economical & Reliable Result!

- UZIN PE 480: barrier against moisture up to 100%RH
- UZIN PE 280: bonding agent for renovation work
- UZIN NC 170: self levelling to a minimum of 2mm



SPECTRUM

To find out more please contact Spectrum Floors on 1300 786 585 / EMAIL: uzin@spectrumfloors.com.au

SPECTRUM Damp Proof Membrane

Challenge

You are working on a concrete or cement screed floor you will need to install a moisture proof membrane which both strengthens and protects it against any possible sub-floor moisture, particularly if you are going to cover with a resilient vinyl or carpet flooring. The challenge is that most damp proofing products on the market have long drying times, which inevitably lead to delays in the project or multiple trips to the site.

Solution

The Uzin PE 480, 2 part Epoxy Primer, now solves these issues as it simply requires a single application thereby significantly reducing the preparation time prior to the flooring installation. It also strengthens the surface and creates a tough and impenetrable damp-proofing membrane, even on cement based substrates with very high moisture content.



Give the floor a light sand with a sanding machine to remove loose and weak particles such as paint or sediments to create a good key for the Epoxy damp-proof membrane.



Punch several times through the plastic plug and the base of the top section of combi-container using a metal spike (or screwdriver). Wear protective clothing! Allow the liquid hardener to drain completely into the resin container.



Once the part B (upper section) of the combi-can is completely drained discard the upper section.



Mix both components of UZIN PE 480 in the container thoroughly using a drill with mixer attachment until streak-free.



Immediately apply an even coat of the UZIN PE 480 using a B1 notched trowel.



As soon as UZIN PE 480 is dry enough to accept foot traffic, but no later than 36 hours, apply one coat UZIN PE 280 using a nylon fibre roller.



Scan this QR barcode on your Smartphone with a QR barcode scanner to give you a direct link to Spectrum Floors.

quality
innovation
experience
service

© Spectrum Floors – 05/2013


SPECTRUM'S COMPLETE PACKAGE

The Right Choice For You

At Spectrum, a family business and 100% Australian owned, we supply the whole package. From sub-floor preparation, right through to the finishing touches, with quality products and technical know-how sourced from leading manufacturers internationally.

This, combined with our excellent customer service ensures...

Spectrum's The Right Choice For You!



Plus Adhesives, Screeds, Tools & A Whole Lot More!

"Spectrum Floors...Your Unpaid Flooring Consultants!"

CALL US TODAY!

...for innovative products, guaranteed results and lasting satisfaction..

1300 786 585



SPECTRUM FLOORS

AUST. PTY LTD
ABN 62 567 829 899

Need information and inspiration for your design? [Here's what other Professionals are using.](#)

<http://www.spectrumfloors.com.au>

☎ 1300 786 585 | 📠 1300 786 587 | 🌐 www.spectrumfloors.com.au | ✉ 393@spectrumfloors.com.au

🏠 8 Selgar Ave Clovelly Park SA 5042



Quality | Experience | Service | Innovation

Copyright © 2014 | Spectrum Floors Aust. Pty Ltd | All rights reserved.

Our mailing address is:

SPECTRUM FLOORS (AUST.) PTY. LTD.,
PO BOX 246
MELROSE PARK SA 5039

[unsubscribe from this list](#) [update subscription preferences](#)